

# COMPOSITE DRY WALL BUSHING

## Index

DCI-10/200~630.....	2
DCI-40.5/630~3150.....	3
DCI-66/630~1600.....	4
DCI-110/630~1600.....	5
DCI-20/1000~4000 .....	6

⚡ DCI-10/200~630



Product Model	DCI-10/200~630
Rated Voltage (kV)	10
Rated Current (A)	200~630
Lightning Impulse withstand Voltage (peak) (kV)	75
P.F.wet withstand Voltage (Virtual Value) (kV)	30
Bending break load (N)	1250
Permitted bending load (N)	625

 **DCI-40.5/630~3150**



Product Model	DCI-40.5/630~3150
Rated Voltage (kV)	35
Rated Current (A)	630~3150
Lightning Impulse withstand Voltage (peak) (kV)	200
P.F.wet withstand Voltage (Virtual Value) (kV)	80
Bending break load (N)	1250
Permitted bending load (N)	625

 DCI-66/630~1600



Product Model	DCI-66/630~1600
Rated Voltage (kV)	66
Rated Current (A)	630~1600
Lightning Impulse withstand Voltage (peak) (kV)	325
P.F.wet withstand Voltage (Virtual Value) (kV)	147
Bending break load (N)	1250
Permitted bending load (N)	625

 DCI-110/630~1600



Product Model	DCI-110/630~1600
Rated Voltage (kV)	110
Rated Current (A)	630~1600
Lightning Impulse withstand Voltage (peak) (kV)	550
P.F.wet withstand Voltage (Virtual Value) (kV)	230
Bending break load (N)	1250
Permitted bending load (N)	625

**DCI-20/1000~4000**



Product Model	DCI-20/1000~4000
Rated Voltage (kV)	20
Rated Current (A)	1000~4000
Lightning Impulse withstand Voltage (peak) (kV)	125
P.F.wet withstand Voltage (Virtual Value) (kV)	50
Bending break load (N)	1250
Permitted bending load (N)	625